NSN 5930-01-023-6947

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-023-6947

Hazardous Locations/environmental Protection:
Watertight
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.531 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.156 inches
Housing Height:
2.094 inches
Housing Length:
6.188 inches
Housing Width:
2.469 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.125 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.078 inches
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts: 575.0 ac
575.0 ac
575.0 ac Inclosure Type:
575.0 ac Inclosure Type: Fully enclosed
575.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement:
575.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
575.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force:
575.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces
575.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force:
575.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage:
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Shelf Life:
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Shelf Life: N/a
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Shelf Life: N/a
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Shelf Life: N/a Unit Of Measure:
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 8.0 inch-ounces Switch Actuating Force: 16.0 inch-ounces Contact Load Current Rating At Maximum Rated Voltage: 1.200 amperes resistive ac Shelf Life: N/a Unit Of Measure: Demilitarization: