

View Online at <https://aerobasegroup.com/nsn/5930-01-023-8289>

Thread Class:

2b all pressure connection

Inside Diameter:

0.438 inches all connections

Overall Length:

6.750 inches

Overall Height:

7.750 inches

Overall Width:

2.875 inches

Body Height:

4.625 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.00/+15.00 actuation point inches of water and +3.00/+15.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Pressure Connector Type:

Double compression, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0