

View Online at <https://aerobasegroup.com/nsn/5930-01-023-8289>

**Thread Class:**

2b all pressure connection

**Inside Diameter:**

0.438 inches all connections

**Overall Length:**

6.750 inches

**Overall Height:**

7.750 inches

**Overall Width:**

2.875 inches

**Body Height:**

4.625 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Mounting Facility Centers:**

5.250 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

60.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+3.00/+15.00 actuation point inches of water and +3.00/+15.00 deactuation point inches of water

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

550.0 ac at sea level first voltage

**Pressure Connector Type:**

Double compression, threaded internal all connections

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0