NSN 5930-01-023-8295

Thermostatic Switch - Page 1 of 2

Gas or liquid



View Online at https://aerobasegroup.com/nsn/5930-01-023-8295

| Overall Length: |
|---|
| 4.875 inches |
| Overall Height: |
| 6.156 inches |
| Overall Width: |
| 2.875 inches |
| Body Height: |
| 2.500 inches |
| Capillary Tube Length: |
| 3.0 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.406 inches |
| Shortest Horizontal Distance Between Mounting Centers: |
| 1.750 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 3.281 inches |
| Tempurature Sensing Element Type: |
| Capillary tube |
| Mounting Method: |
| Bracket |
| Features Provided: |
| Electrical access port |
| Contact Action Stimulus: |
| Decrease |
| Mounting Facility Pattern: |
| Isosceles triangle |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double break/double make, one position momentary |
| Terminal Type: |
| Tab w/screw |
| Contact Load Current Rating: |
| 3.2 amperes resistive load first voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |
| Contact Adjustment Range: |
| +140.00/+215.00 actuation point degrees fahrenheit and +136.00/+211.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External deactuation point screw and external actuation point screw |
| Contact Voltage Rating In Volts: |
| 550.0 ac at sea level first voltage |
| Media For Which Designed: |

NSN 5930-01-023-8295

Thermostatic Switch - Page 2 of 2



| Style Designator: |
|-------------------|
| Rectangular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

Fiig:

A048b0