

View Online at <https://aerobasegroup.com/nsn/5930-01-023-9210>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Overall Length:**

4.875 inches

**Overall Height:**

5.406 inches

**Overall Width:**

2.875 inches

**Body Height:**

2.750 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 580.0 degrees fahrenheit

**Mounting Method:**

Bracket

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

216.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

3.2 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+10.00/+180.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

550.0 ac at sea level first voltage

**Pressure Connector Type:**

Inverted flare, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unef single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0