

View Online at <https://aerobasegroup.com/nsn/5930-01-023-9825>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

9.813 inches

Overall Height:

2.938 inches

Overall Width:

2.500 inches

Shaft Length:

3.125 inches single actuator

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

5

Knob Manufacturer Code:

03497

Knob Manufacturer Part Number:

K-6208137-1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section front

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

550.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load lowest dc voltage rating at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0