

View Online at <https://aerobasegroup.com/nsn/5930-01-024-1922>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.497 inches and 0.503 inches

Body Length:

1.156 inches

Body Width:

0.250 inches

Body Height:

1.188 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.370 inches and 0.376 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.094 inches

Actuator Free Position Height:

Between 0.386 inches and 0.406 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

3 pole, double throw, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 8.000 amperes resistive ac

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0