

View Online at <https://aerobasegroup.com/nsn/5930-01-024-2823>

**Unthreaded Mounting Hole Diameter:**

0.250 inches single mounting facility

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

30086

**Longest Horizontal Distance Between Mounting Centers:**

1.875 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.688 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

600.0 highest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

8.0 amperes resistive load highest ac voltage rating at sea level and 6.0 amperes inductive load highest ac voltage rating at sea level

**Style Designator:**

Square wafer, panel mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0