

View Online at <https://aerobasegroup.com/nsn/5930-01-024-2823>

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

1

Knob Manufacturer Code:

30086

Longest Horizontal Distance Between Mounting Centers:

1.875 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.688 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 highest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

8.0 amperes resistive load highest ac voltage rating at sea level and 6.0 amperes inductive load highest ac voltage rating at sea level

Style Designator:

Square wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0