View Online at https://aerobasegroup.com/nsn/5930-01-024-2831

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Bushing Length:**

0.310 inches

**Body Length:**

1.183 inches

**Body Width:**

0.790 inches

**Body Height:**

1.185 inches

**Actuator Diameter:**

0.323 inches

**Actuator Height:**

0.190 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole,  double throw,  one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab,  solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0