NSN 5930-01-024-3578

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-024-3578

Body Style:		
Panel mounted		
Hazardous Locations/environmental Protection:		
Explosion proof and humidity resistant		
Overall Length:		
3.635 inches		
Overall Height:		
0.750 inches		
Overall Width:		
0.750 inches		
Body Width:		
0.750 inches		
Body Height:		
0.750 inches		
Case Material:		
Metal		
Actuator Length:		
0.625 inches		
Actuator Style:		
Rectangular		
Actuator Height:		
0.100 inches		
Actuator Width:		
0.625 inches		
Actuator Color:		
Black single actuator		
Illuminated Actuator Color:		
Green single actuator and amber single actuator		
Actuator Inscription:		
Open close single actuator		
Illuminated Actuator Color Sequence:		
Upper half of actuator green lower half of actuator amber		
Maximum Voltage Rating In Volts:		
115.0 ac and 28.0 dc		
Mounting Surface To Terminal End Distance:		
3.135 inches		
Inclosure Type:		
Fully enclosed		
Mounting Method:		

Full display lens

Features Provided:

Panel

NSN 5930-01-024-3578

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Special	Features:
---------	-----------

Removable dim/test contact module

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

15 pin

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0