

View Online at <https://aerobasegroup.com/nsn/5930-01-024-3579>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.635 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.625 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.625 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Green single actuator and white single actuator

Actuator Inscription:

Off single actuator

Illuminated Actuator Color Sequence:

Left half of actuator green right half of actuator white

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.535 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Removable dim/test contact module

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0