## NSN 5930-01-024-4224

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-024-4224 **Thread Class:** 2b 2nd mounting facility Thread Length: 0.188 inches 1st mounting facility **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 9.219 inches **Overall Height:** 2.813 inches **Overall Width:** 2.813 inches **Shaft Length:** 1.312 inches single actuator **Individual Section Quantity:** 14 **Knob Manufacturer Code:** 82121 **Longest Horizontal Distance Between Mounting Centers:** 2.296 inches 2nd mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.296 inches 2nd mounting facility **Operating Tempurature Range:** -20.0/+160.0 degrees fahrenheit **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded hole 2nd mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 2nd mounting facility **Thread Size:** 0.625 inches 1st mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular 2nd mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator

**Shaft Type:** 

Rectangular/square, threaded hole single actuator

## **NSN 5930-01-024-4224**Rotary Switch - Page 2 of 2



Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unef 1st mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0