

View Online at <https://aerobasegroup.com/nsn/5930-01-024-4225>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.188 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

11.844 inches

**Overall Height:**

2.813 inches

**Overall Width:**

2.813 inches

**Shaft Length:**

1.312 inches single actuator

**Individual Section Quantity:**

20

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

2.296 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.296 inches 2nd mounting facility

**Operating Temperature Range:**

-20.0/+160.0 degrees fahrenheit

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 2nd mounting facility

**Thread Size:**

0.625 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0