## NSN 5930-01-024-4236

View Online at https://aerobasegroup.com/nsn/5930-01-024-4236

Sensitive Switch - Page 1 of 2

**Thread Class:** 

Unef



2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Body Length:** Between 0.771 inches and 0.791 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.345 inches and 0.375 inches **Case Material: Plastic Actuator Style:** Roller arm **Actuator Free Position Height:** Between 0.500 inches and 0.620 inches **Actuator Roller Diameter:** 0.188 inches **Actuator Roller Width:** 0.125 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thread Size: 0.375 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, two positions momentary single switch unit **Switch Release Force:** 4.0 grams **Switch Actuating Force:** 18.0 grams **Actuator Movement:** Between 0.085 pretravel inches and 0.011 overtravel inches and 0.019 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 4.000 amperes resistive ac **Thread Series Designator:** 

## NSN 5930-01-024-4236

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0