

View Online at <https://aerobasegroup.com/nsn/5930-01-024-4236>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.345 inches and 0.375 inches

Case Material:

Plastic

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 0.500 inches and 0.620 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Release Force:

4.0 grams

Switch Actuating Force:

18.0 grams

Actuator Movement:

Between 0.085 pretravel inches and 0.011 overtravel inches and 0.019 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0