

View Online at <https://aerobasegroup.com/nsn/5930-01-024-4237>

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.345 inches and 0.375 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.092 inches

**Actuator Length:**

0.680 inches

**Actuator Style:**

Leaf

**Actuator Free Position Height:**

Between 0.592 inches and 0.662 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Switch Release Force:**

2.0 grams

**Switch Actuating Force:**

15.0 grams

**Actuator Movement:**

0.240 pretravel inches and 0.050 overtravel inches and 0.062 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0