

View Online at <https://aerobasegroup.com/nsn/5930-01-024-4238>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.345 inches and 0.375 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.092 inches

Actuator Length:

0.580 inches

Actuator Style:

Leaf

Actuator Free Position Height:

Between 0.592 inches and 0.662 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Release Force:

2.0 grams

Switch Actuating Force:

15.0 grams

Actuator Movement:

0.240 pretravel inches and 0.050 overtravel inches and 0.062 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes inductive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0