

View Online at <https://aerobasegroup.com/nsn/5930-01-024-4379>

Hazardous Locations/environmental Protection:

Dripproof and dustproof

Overall Length:

3.610 inches

Overall Height:

2.090 inches

Overall Width:

2.600 inches

Unthreaded Mounting Hole Diameter:

0.140 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

3.334 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.200 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

9 4th actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 4th section

Contact Arrangement Truth Table:

Bcd with complement, 2 pole - 10 positions each section

Color:

Clear each lamp

Precious Material And Location:

Printed circuit board surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0