NSN 5930-01-024-5544

Sensitive Switch - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5930-01-024-5544

Hazardous Locations/environmental Protection:
Dustproof
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Height:
0.500 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.875 inches
Housing Length:
4.685 inches
Housing Width:
1.785 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit
Switch Actuating Force:
64.0 inch-ounces
Actuator Movement:
18.0 pretravel degrees and 57.0 overtravel degrees and 10.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
400.000 milliamperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes resistive ac
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5930-01-024-5544 Sensitive Switch - Page 2 of 2



Fiig:

A053a0