

View Online at <https://aerobasegroup.com/nsn/5930-01-024-9174>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.482 inches and 0.502 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.089 inches

Actuator Length:

1.000 inches

Actuator Style:

Leaf

Actuator Width:

Between 0.060 inches and 0.080 inches

Actuator Free Position Height:

0.335 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 grams

Switch Actuating Force:

15.0 grams

Actuator Movement:

0.240 pretravel inches and 0.050 overtravel inches and 0.062 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0