NSN 5930-01-024-9174

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-024-9174

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.370 inches and 0.380 inches
Body Length:
Between 0.771 inches and 0.791 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.482 inches and 0.502 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.089 inches
Actuator Length:
1.000 inches
Actuator Style:
Leaf
Actuator Width:
Between 0.060 inches and 0.080 inches
Actuator Free Position Height:
0.335 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 grams
Switch Actuating Force:
15.0 grams
Actuator Movement:
0.240 pretravel inches and 0.050 overtravel inches and 0.062 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

NSN 5930-01-024-9174

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0