NSN 5930-01-025-0877

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-025-0877

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.823 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.493 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Leaf
Actuator Width:
0.130 inches
Actuator Free Position Height:
0.399 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole and slot
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 grams
Switch Actuating Force:
12.0 grams
Actuator Movement:
Between 0.455 pretravel inches and 0.026 overtravel inches and 0.015 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
3 tab, solder lug

NSN 5930-01-025-0877

Sensitive Switch - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0