

View Online at <https://aerobasegroup.com/nsn/5930-01-025-0878>

**Body Style:**

Hole mounted

**Overall Length:**

0.863 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

0.823 inches

**Overall Width:**

0.250 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.493 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Length:**

0.660 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.130 inches

**Actuator Free Position Height:**

0.340 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole and slot

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

3.0 grams

**Switch Actuating Force:**

16.0 grams

**Actuator Movement:**

Between 0.340 pretravel inches and 0.019 overtravel inches and 0.014 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0