

View Online at <https://aerobasegroup.com/nsn/5930-01-025-2221>

**Inside Diameter:**

0.188 inches all connections

**Overall Length:**

2.000 inches

**Outside Diameter:**

0.200 inches all connections

**Overall Height:**

1.312 inches

**Overall Width:**

0.475 inches

**Body Length:**

1.125 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.091 inches and 0.097 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.719 inches

**Longest Vertical Distance Between Mounting Centers:**

0.719 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Base and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

10.00 pounds per square inch gage

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

20.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

0.15 actuation point inches of water

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Barbed, unthreaded external all connections

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0