

View Online at <https://aerobasegroup.com/nsn/5930-01-025-2221>

Inside Diameter:

0.188 inches all connections

Overall Length:

2.000 inches

Outside Diameter:

0.200 inches all connections

Overall Height:

1.312 inches

Overall Width:

0.475 inches

Body Length:

1.125 inches

Unthreaded Mounting Hole Diameter:

Between 0.091 inches and 0.097 inches

Longest Horizontal Distance Between Mounting Centers:

0.719 inches

Longest Vertical Distance Between Mounting Centers:

0.719 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

10.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

20.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

0.15 actuation point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0