

View Online at <https://aerobasegroup.com/nsn/5930-01-025-2245>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

0.990 inches

Bushing Length:

0.440 inches

Body Length:

1.090 inches

Actuator Diameter:

0.380 inches

Actuator Height:

0.280 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Aircraft, galaxy c-5

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0