

View Online at <https://aerobasegroup.com/nsn/5930-01-025-7173>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

4.130 inches

**Overall Height:**

4.190 inches

**Overall Width:**

3.500 inches

**Mounting Slot Width:**

0.280 inches

**Body Length:**

4.130 inches

**Distance Between Mounting Facility Centers:**

2.500 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Slot

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Decrease

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

10.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.03/+2.89 actuation point pounds per square inch and +0.14/+3.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point dial and internal deactuation point dial

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Gasket seal, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0