## NSN 5930-01-025-7173

Pressure Switch - Page 1 of 2

480.0 ac at sea level first voltage



View Online at https://aerobasegroup.com/nsn/5930-01-025-7173

Inside Diameter:
0.250 inches single connection
Overall Length:
4.130 inches
Overall Height:
4.190 inches
Overall Width:
3.500 inches
Mounting Slot Width:
0.280 inches
Body Length:
4.130 inches
Distance Between Mounting Facility Centers:
2.500 inches
Pressure Switch Type:
Differential
Mounting Method:
Slot
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
10.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.03/+2.89 actuation point pounds per square inch and +0.14/+3.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point dial and internal deactuation point dial
Contact Voltage Rating In Volts:

## NSN 5930-01-025-7173

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Gasket seal, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0