

View Online at <https://aerobasegroup.com/nsn/5930-01-025-7173>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.130 inches

Overall Height:

4.190 inches

Overall Width:

3.500 inches

Mounting Slot Width:

0.280 inches

Body Length:

4.130 inches

Distance Between Mounting Facility Centers:

2.500 inches

Pressure Switch Type:

Differential

Mounting Method:

Slot

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.03/+2.89 actuation point pounds per square inch and +0.14/+3.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point dial and internal deactuation point dial

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0