

View Online at <https://aerobasegroup.com/nsn/5930-01-025-7174>

Thread Class:

2a all pressure connection

Thread Length:

0.438 inches all pressure connection

Hazardous Locations/environmental Protection:

Dustproof and watertight and vibration resistant

Outside Diameter:

0.438 inches all connections

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch gage

Thread Size:

0.438 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load eighth voltage

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Pressure Connector Type:

Flared, threaded external all connections

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0