

View Online at <https://aerobasegroup.com/nsn/5930-01-025-7183>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

1.344 inches

Body Length:

3.040 inches

Body Width:

1.000 inches

Body Height:

1.060 inches

Case Material:

Metal

Actuator Length:

1.562 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.906 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.312 inches

Housing Length:

2.460 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.750 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0