NSN 5930-01-025-7184

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-025-7184

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

1.406 inches

Actuator Style:

Leaf

Actuator Width:

0.110 inches

Actuator Free Position Height:

0.609 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

100.0 grams

Switch Actuating Force:

144.0 grams

Actuator Movement:

Between 0.125 pretravel inches and 0.090 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

NSN 5930-01-025-7184

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0