NSN 5930-01-025-7184

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-025-7184		
Body Style:		
Hole mounted		
Hazardous Locations/environmental Protection:		
Dustproof		
Center To Center Distance Between Mounting Facilities Parallel To Length:		
0.875 inches		
Body Length:		
1.094 inches		
Body Width:		
0.406 inches		
Body Height:		
0.625 inches		
Case Material:		
Plastic		
Unthreaded Mounting Hole Diameter:		
0.114 inches		
Center To Center Distance Between Mounting Facilities Parallel To Height:		
0.406 inches		
Actuator Length:		
1.406 inches		
Actuator Style:		
Leaf		
Actuator Width:		
0.110 inches		
Actuator Free Position Height:		
0.609 inches		
Maximum Voltage Rating In Volts:		
250.0 ac		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Unthreaded hole		

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

100.0 grams

Switch Actuating Force:

144.0 grams

Actuator Movement:

Between 0.125 pretravel inches and 0.090 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

NSN 5930-01-025-7184

Sensitive Switch - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0