

View Online at <https://aerobasegroup.com/nsn/5930-01-025-7844>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Body Diameter:

1.500 inches

Bushing Length:

1.000 inches

Body Length:

Between 2.395 inches and 2.595 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

Between 0.345 inches and 0.405 inches

Actuator Free Position Height:

Between 1.345 inches and 1.405 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

80.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0