

View Online at <https://aerobasegroup.com/nsn/5930-01-025-7844>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Body Diameter:**

1.500 inches

**Bushing Length:**

1.000 inches

**Body Length:**

Between 2.395 inches and 2.595 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

Between 0.345 inches and 0.405 inches

**Actuator Free Position Height:**

Between 1.345 inches and 1.405 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

80.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 6.000 amperes inductive dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0