

View Online at <https://aerobasegroup.com/nsn/5930-01-025-9213>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches

Bushing Length:

0.625 inches

Body Length:

2.500 inches

Body Width:

0.812 inches

Body Height:

1.125 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.406 inches

Actuator Free Position Height:

Between 0.263 inches and 0.289 inches

Maximum Voltage Rating In Volts:

110.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Actuating Force:

Between 10.0 ounces and 14.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0