NSN 5930-01-025-9647

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-025-9647 **Thread Class:** 2b all threaded hole **Overall Length:** 2.750 inches **Overall Height:** 7.312 inches **Overall Width:** 2.875 inches **Body Height:** 3.812 inches **Capillary Tube Length:** 72.0 inches **Bulb Length:** 4.125 inches **Bulb Diameter:** 0.375 inches **Longest Horizontal Distance Between Mounting Centers:** 1.906 inches **Longest Vertical Distance Between Mounting Centers:** 2.438 inches **Tempurature Sensing Element Type:** Capillary tube-bulb **Mounting Method:** Threaded hole **Features Provided:** Tamper proof cap Thready Qty Per Inch (tpi): 32 all threaded hole **Contact Action Stimulus:** Increase **Thread Size:** 0.164 inches all threaded hole **Mounting Facility Pattern:**

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

NSN 5930-01-025-9647

Thermostatic Switch - Page 2 of 2



Contact Adjustment Range:

+50.00/+250.00 actuation point degrees fahrenheit and +48.00/+248.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0