

View Online at <https://aerobasegroup.com/nsn/5930-01-025-9647>

**Thread Class:**

2b all threaded hole

**Overall Length:**

2.750 inches

**Overall Height:**

7.312 inches

**Overall Width:**

2.875 inches

**Body Height:**

3.812 inches

**Capillary Tube Length:**

72.0 inches

**Bulb Length:**

4.125 inches

**Bulb Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.906 inches

**Longest Vertical Distance Between Mounting Centers:**

2.438 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Threaded hole

**Features Provided:**

Tamper proof cap

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.164 inches all threaded hole

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+50.00/+250.00 actuation point degrees fahrenheit and +48.00/+248.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0