

View Online at <https://aerobasegroup.com/nsn/5930-01-025-9653>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Body Height:

Between 0.940 inches and 0.980 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.405 inches and 0.435 inches

Actuator Height:

Between 1.035 inches and 1.065 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position momentary

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and center position no locking action

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0