

View Online at <https://aerobasegroup.com/nsn/5930-01-026-1020>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Flame resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.497 inches and 0.503 inches

Bushing Length:

0.125 inches

Body Length:

1.250 inches

Body Width:

0.515 inches

Body Height:

0.890 inches

Unthreaded Mounting Hole Diameter:

0.115 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.125 inches

Actuator Width:

0.250 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

4 two circuit, double break/double make, permanent jumper with no external terminal, both positions maintained single switch unit

Switch Release Force:

400.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 6.000 amperes motor ac

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0