

View Online at <https://aerobasegroup.com/nsn/5930-01-026-1020>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Flame resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.497 inches and 0.503 inches

**Bushing Length:**

0.125 inches

**Body Length:**

1.250 inches

**Body Width:**

0.515 inches

**Body Height:**

0.890 inches

**Unthreaded Mounting Hole Diameter:**

0.115 inches

**Actuator Length:**

0.250 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.125 inches

**Actuator Width:**

0.250 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

4 two circuit, double break/double make, permanent jumper with no external terminal, both positions maintained single switch unit

**Switch Release Force:**

400.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 6.000 amperes motor ac

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0