

View Online at <https://aerobasegroup.com/nsn/5930-01-026-3813>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

Between 0.606 inches and 0.626 inches

Body Width:

Between 0.306 inches and 0.326 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

Between 0.086 inches and 0.091 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.060 inches

Actuator Height:

0.145 inches

Actuator Free Position Height:

Between 0.455 inches and 0.475 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

61.0 in. Nom o/a lg

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0