NSN 5930-01-026-5946

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-026-5946

| Body Style: |
|--|
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Body Length: |
| 1.380 inches |
| Body Width: |
| 0.390 inches |
| Body Height: |
| 1.237 inches |
| Actuator Length: |
| 0.267 inches |
| Actuator Style: |
| Roller arm |
| Actuator Free Position Height: |
| 0.687 inches |
| Actuator Roller Diameter: |
| 0.211 inches |
| Actuator Roller Width: |
| 0.156 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| Aitcraft, eagle f-15 |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Method: |
| Threaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 12.0 ounces |
| Criticality Code Justification: |
| Feat |
| Switch Actuating Force: |
| 48.0 ounces |
| Actuator Movement: |
| 0.040 pretravel inches and 0.075 overtravel inches and 0.030 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes motor dc |
| Special Features: |

Weapon system essential

NSN 5930-01-026-5946

Sensitive Switch - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

Fiig:

A053a0