

View Online at <https://aerobasegroup.com/nsn/5930-01-026-6361>

**Thread Class:**

3b all pressure connection

**Inside Diameter:**

0.438 inches all connections

**Thread Length:**

0.656 inches all pressure connection

**Overall Length:**

4.000 inches

**Body Length:**

0.570 inches

**Overall Diameter:**

2.500 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -67.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Base

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

120.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Sensing Element Burst Pressure:**

180.00 pounds per square inch

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

4.00 actuation point pounds per square inch and 1.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

440.0 ac at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0