

View Online at <https://aerobasegroup.com/nsn/5930-01-026-6370>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Overall Length:

2.563 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.308 inches

Overall Width:

0.641 inches

Body Length:

1.812 inches

Body Width:

0.641 inches

Body Height:

0.641 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.145 inches

Actuator Style:

Round

Actuator Free Position Height:

0.812 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole and threaded bushing

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.187 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0