NSN 5930-01-026-6843

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-026-6843 **Overall Length:** 3.600 inches **Overall Width:** 3.600 inches **Body Diameter:** 2.400 inches **Unthreaded Mounting Hole Diameter:** 0.210 inches **Distance Between Mounting Facility Centers:** 3.000 inches **Pressure Switch Type:** Gage **Mounting Method:** Flange and unthreaded hole **Contact Action Stimulus:** Increase **Proof Pressure:** 120.00 pounds per square inch **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, double throw, two positions momentary **Sensing Element Burst Pressure:** 180.00 pounds per square inch **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 4.00 actuation point pounds per square inch and 1.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch **Contact Voltage Rating In Volts:** 28.0 dc at sea level single voltage Media For Which Designed: Liquid

N/a

Unit Of Measure:

Shelf Life:

Style Designator:

Cylindrical w/mounting lugs

NSN 5930-01-026-6843

Pressure Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0