

View Online at <https://aerobasegroup.com/nsn/5930-01-026-8590>

Thread Class:

2b

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.560 inches and 0.584 inches

Body Length:

Between 0.874 inches and 0.898 inches

Body Width:

Between 0.535 inches and 0.545 inches

Body Height:

Between 0.720 inches and 0.780 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.247 inches

Actuator Height:

1.030 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Nonpile-up Contact Arrangement:

1 two circuit, double make, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0