## NSN 5930-01-026-9669

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-026-9669

### **Body Style:**

Hole mounted

### **Hazardous Locations/environmental Protection:**

Moisture resistant

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

### **Body Length:**

Between 1.925 inches and 1.955 inches

### **Body Width:**

Between 0.677 inches and 0.697 inches

### **Body Height:**

Between 0.850 inches and 0.910 inches

#### **Case Material:**

Plastic

### **Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

### **Switch Actuator Quantity:**

1

### **Actuator Length:**

1.620 inches

### **Actuator Style:**

Leaf

### **Actuator Width:**

Between 0.175 inches and 0.205 inches

### **Actuator Free Position Height:**

0.969 inches

### **Maximum Voltage Rating In Volts:**

125.0 ac and 250.0 dc

#### **Inclosure Type:**

Fully enclosed

### **Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

### Switch Release Force:

1.0 ounces

### **Switch Actuating Force:**

12.0 ounces

### **Actuator Movement:**

0.060 overtravel inches

### **Contact Load Current Rating At Maximum Rated Voltage:**

1.900 amperes resistive dc and 10.000 amperes resistive ac

### **Terminal Type And Quantity:**

3 screw

# NSN 5930-01-026-9669

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0