## NSN 5930-01-027-3245



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-027-3245 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Oiltight Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches **Body Width: 2.313 inches Center To Center Distance Between Mounting Facilities Parallel To Height:** 3.688 inches **Actuator Length:** 6.125 inches **Actuator Style:** Roller arm **Actuator Height:** 2.750 inches **Actuator Roller Diameter:** 1.000 inches **Actuator Roller Width:** 0.313 inches **Maximum Voltage Rating In Volts:** 575.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thread Size: 0.190 inches **Nonpile-up Contact Arrangement:** 2 two circuit, two positions momentary single switch unit **Switch Release Force:** 10.0 inch-ounces **Switch Actuating Force:** 32.0 inch-ounces **Actuator Movement:** 15.0 pretravel degrees and 20.0 overtravel degrees and 20.0 differential degrees **Contact Load Current Rating At Maximum Rated Voltage:** 12.000 amperes resistive ac

**Thread Series Designator:** 

Unf

## NSN 5930-01-027-3245

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0